

ES132

HIGH TEMPERATURE
HIGH STRENGTH
CONTACT ADHESIVE

Specifically designed for
Air Assist Spray

Nonflammable


No ODS

EverStrong™ Bond
Performance

High Temperature
Resistance

Fast Tack

Water Resistant



EVERSTRONG
ADHESIVE

AIR ASSIST SPRAY

EverStrong™ ES132 is a non-flammable high performance versatile industrial strength contact adhesive specifically designed for air assist spray. Water resistant and temperature resistant to over 200°F, ES132 is designed for bonding a wide range of substrates to include decorative laminates and veneers, fiberglass, glass, upholstery, fabrics, foam, auto headliners, cork and particle board.

PRODUCT USAGE

EverStrong™ ES132 is designed to be applied to both surfaces about to be joined. Spray an even coat of adhesive with at least 80% to 100% coverage of each surface. Allow to dry 3-5 minutes until tacky. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease, oil or other contaminants. Ensure that the adhesives and substrates are at 60°F or higher. If surfaces are porous, a second coat is recommended after the first has dried and become tacky.

STORAGE

After use, do not close the valve. Leave the gun and hose connected to the canister. Recommended to store canister off the floor if temperatures below 60°F.

PHYSICAL PROPERTIES

Appearance:	Liquid, clear or red
Specific Gravity:	.145+/- .03
Shear Adhesion:	>100psi and >200°F
Spray Pattern:	Web Spray
Flammability:	Nonflammable per ASTM E-681-04
Solvent:	Trichloroethylene
Shelf Life:	15 months
Freezing:	Not damaged by freezing but return to room temp before use.

PACKAGING

ES132-009C(R)	9 lbs Disposable Canister
ES132-038C(R)	38 lbs Disposable Canister
ES132-190C(R)	190 lbs Returnable Canister
ES132-375(R)	375 lbs Returnable Canister

All available in Clear (C) or Red (R)

KEY FEATURES

- ★ Specifically designed for Air Assist Spray
- ★ Nonflammable
- ★ No ODS (Ozone depleting substances)
- ★ EverStrong™ Bond Performance
- ★ High Temperature Resistance
- ★ Fast Tack
- ★ Water Resistant



Disclaimer of Warranty: NewStar Adhesives Inc. expressly disclaims all warranties either expressed or implied, including but not limited to merchantability and fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost, at our discretion. This provision relates to all sales and cannot be modified.

Manufacturer: NewStar Adhesives Inc., gluepros@newstaradhesives.com, 855-497-0700

See MSDS Data Sheet for Proper Handling and Safety Information

ES132-1

