



EVERSTRONG[™] ADHESIVE

ES10^{ET}

SCAQMD Rule 1168
Compliant

OTC Compliant

LEED Compliant

Flammable DOT

Postformable

EverStrong[™] Bond
Performance

Fast Tack

High Temperature
resistance

Extended Open Time

EverStrong[™] ES10 ET is a high performance industrial strength contact adhesive formulated for longer open time and to comply with CA and OTC state regulations. Water resistant and temperature resistant to over 200°F, ES10 is designed for bonding a wide range of substrates to include decorative laminates and veneers, fiberglass, glass, upholstery, fabrics, foam, auto headliners, cork and particle board.

PRODUCT USAGE

EverStrong[™] ES10 ET is designed to be applied to both surfaces about to be joined. Spray an even coat of adhesive with at least 80% to 100% coverage of each surface. Allow to dry 3-5 minutes til tacky. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease or oil. Ensure that the adhesives and substrates are at 60°F or higher. If surfaces are porous, a second coat is recommended after the first has dried and become tacky.

STORAGE

After use, do not close the valve. Leave the gun and hose connected to the canister. Recommended to store canister off the floor if temperatures below 60°F.

PHYSICAL PROPERTIES

Appearance:	Liquid, clear or red
Specific Gravity:	.95 + .02
Shear Adhesion:	>100psi and >200°F
Spray Tip:	ES4001
Spray Pattern:	Pebble Spray
Flammability:	Flammable per ASTM E-681-04
VOC:	No ODS, No HAPS
Shelf Life:	15 months
Freezing:	Not damaged by freezing but return to room temp before use.

PACKAGING

ES10 ET-013C(R)	Available in ES10+ Aerosol (ES10Plus-013)
ES10 ET-008C(R)	8 lbs Disposable Canister
ES10 ET-030C(R)	27 lbs Disposable Canister
ES10 ET-140C(R)	130 lbs Returnable Canister
ES10 ET-280C(R)	270 lbs Returnable Canister
ES10 ET-005C(R)	5 gal Pail
ES10 ET-055C(R)	55 gal Drum

All available in Clear (C) or Red (R)

Disclaimer of Warranty: NewStar Adhesives Inc. expressly disclaims all warranties either expressed or implied, including but not limited to merchantability and fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost, at our discretion. This provision relates to all sales and cannot be modified.

Manufacturer: NewStar Adhesives Inc., gluepros@newstaradhesives.com, 855-497-0700

See MSDS Data Sheet for Proper Handling and Safety Information

ES10 ET-1

KEY FEATURES

- ★ SCAQMD Rule 1168 & OTC Compliant
- ★ LEED Compliant
 - LEED Schools EQ Credit 4.0
 - LEED Core & Shell EQ Credit 4.0
 - LEED ND & CI EQ Credit 4.1
 - LEED EB MR Credit 3.0
 - MR Credit 5.1 (specific projects must be evaluated)
- ★ EverStrong[™] Fast Tack Bond Performance
- ★ High Temperature resistance
- ★ Pebble Spray Pattern
- ★ Longer Open Time

