

# ES300

BRUSH GRADE  
CONTACT ADHESIVE



**EVERSTRONG**  
ADHESIVE

Brush Grade

EverStrong™ Bond  
Performance

High Temperature  
Resistance

Fast Tack

EverStrong™ ES300 is a brush grade contact adhesive designed for permanently bonding a wide range of materials. Meets requirements of CPSC. Water resistant and temperature resistant to over 200°F. Suitable for most postforming applications.

## PRODUCT USAGE

EverStrong™ ES300 is designed to be applied to both surfaces about to be joined. Brush or roll an even coat of adhesive on both surfaces. Allow to dry 10-20 minutes until tacky. Place the surfaces together and apply pressure evenly across the full bonding surface from the center out to edges. For best results: Make sure that the surfaces are dry and free from dirt, grease or oil. Ensure that the adhesives and substrates are at 60°F or higher. If assembly is delayed and the adhesive becomes too dry, apply a light coating again. Note: contact adhesive is not repositionable, position pieces to be assembled as required in finished product.

## STORAGE

Store in clean, dry area away from sparks and heat sources. Recommended to store container off the floor if temperatures below 60°F.

## PHYSICAL PROPERTIES

Appearance:	Liquid, clear or red
Base:	Synthetic polymers
Solvent:	Blend of hydrocarbons & ketones
Solids %:	20 – 22%
Density:	6.8 lb/gal
Flash point:	> 20°F
Shelf Life:	12 months (unopened)
Freezing:	Not damaged by freezing but return to room temp & stir before use.

## PACKAGING

ES300-005C(R)	5 gal pail
ES300-055C(R)	55 gal drum

All available in Clear (C) or Red (R)

## KEY FEATURES

- ★ Brush Grade
- ★ EverStrong™ Bond Performance
- ★ High Temperature Resistance
- ★ Fast Tack

**Disclaimer of Warranty:** NewStar Adhesives Inc. expressly disclaims all warranties either expressed or implied, including but not limited to merchantability, fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost. This provision relates to all sales and cannot be modified.

**Manufacturer:** NewStar Adhesives Inc., gluepros@newstaradhesives.com, 855-497-0700

See MSDS Data Sheet for Proper Handling and Safety Information

ES300-1

