

ES700

SPRAY GRADE
CONTACT ADHESIVE



EVERSTRONG[™]
A D H E S I V E

Spray Grade

EverStrong[™] Bond
Performance

High Temperature
Resistance

Fast Tack

EverStrong[™] ES700 is a high solids spray grade contact adhesive designed for mass production. It is suitable for permanently bonding a wide range of materials. Water resistant and temperature resistant to over 200°F. Recommended for flat work applications.

PRODUCT USAGE

EverStrong[™] ES700 is designed to be applied to both surfaces about to be joined. Spray an even coat of adhesive on both surfaces. Allow to tack. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease or oil. Ensure that the adhesives and substrates are at 60°F or higher. If assembly is delayed and the adhesive becomes too dry, apply a light coating again.

STORAGE

Store in clean, dry area away from sparks and heat sources. Recommended to store container off the floor if temperatures below 60°F.

PHYSICAL PROPERTIES

| | |
|--------------|--|
| Appearance: | Liquid, clear or red |
| Base: | Synthetic polymers |
| Solvent: | Blend of hydrocarbons & ketones |
| Solids %: | 12 – 15% |
| Density: | 6.7 lb/gal |
| Flash point: | > -50°F |
| Shelf Life: | 12 months (unopened) |
| Freezing: | Not damaged by freezing but return to room temp & stir before use. |

PACKAGING

| | |
|---------------|-------------|
| ES700-005C(R) | 5 gal Pail |
| ES700-055C(R) | 55 gal Drum |

All available in Clear (C) or Red (R)

KEY FEATURES

- ★ Spray Grade
- ★ EverStrong[™] Bond Performance
- ★ High Temperature Resistance
- ★ Fast Tack
- ★ Flat work Only

Disclaimer of Warranty: NewStar Adhesives Inc. expressly disclaims all warranties either expressed or implied, including but not limited to merchantability and fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost, at our discretion. This provision relates to all sales and cannot be modified.

Manufacturer: NewStar Adhesives Inc., gluepros@newstaradhesives.com, 855-497-0700

See MSDS Data Sheet for Proper Handling and Safety Information

ES700-1

