# ES800 NONFLAMMABLE SPRAY GRADE CONTACT ADHESIVE

Nonflammable Spray Grade

EverStrong™ Bond Performance

High Temperature Resistance

**Fast Tack** 



EverStrong™ ES800 is a nonflammable spray grade neoprene-based contact adhesive suitable for permanently bonding a wide range of materials to include decorative laminates and veneers, fiberglass, glass, cork, particle board and foam. Water resistant and temperature resistant to over 200F.

### PRODUCT USAGE

EverStrong™ ES800 is designed to be applied to both surfaces about to be joined. Spray an even coat of adhesive on both surfaces. Allow to tack. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease or oil. Ensure that the adhesives and substrates are at 60°F or higher. If assembly is delayed and the adhesive becomes too dry, apply a light coating again.

### STORAGE

Store in clean, dry area. Recommended to store container off the floor if temperatures below  $60^{\circ}F$ .

### PHYSICAL PROPERTIES

Appearance: Liquid, clear or green

Base: Neoprene

Solvent: Methylene Chloride

Solids %: 23 – 27% Density: 10.8 lb/gal

Flammability: Nonflammable per ASTM E681-04

Shelf Life: 12 months (unopened)

Freezing: Not damaged by freezing but return to room

temp and stir before use.

# PACKAGING

ES800-005C(G) 5 gal Pail
ES800-055C(G) 55 gal Drum
All available in Clear (C) or Green (G)

## **KEY FEATURES**

- ★ Nonflammable Spray Grade
- **★** EverStrong<sup>™</sup> Bond Performance
- ★ High Temperature Resistance
- ★ Fast Tack

**Disclaimer of Warranty:** NewStar Adhesives Inc. expressly disclaims all warranties either expressed or implied, including but not limited to merchantability and fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost, at our discretion. This provision relates to all sales and cannot be modified.

Manufacturer: NewStar Adhesives Inc., gluepros@newstaradhesives.com, 855-497-0700

See MSDS Data Sheet for Proper Handling and Safety Information

