

# EB70

Flammable DOT

General Purpose Adhesive

Strong Bonds

Fast Tack

No ODS

# EVERBOND

PREMIUM • ADHESIVES

EverBond EB70 is a general purpose industrial strength adhesive formulated to be water resistant and temperature resistant to over 150°F, EB70 is designed for bonding a wide range of substrates to include cardboard, felt, fiberglass, glass, upholstery, fabrics, foam and cork.

## PRODUCT USAGE

For permanent bonds, EverBond EB70 is designed to be applied to both surfaces about to be joined. Spray an even coat of adhesive with at least 80% to 100% coverage of each surface. For temporary bonds, spray only one surface. Allow to dry 3-5 minutes until tacky. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease, oil or other contaminants. Ensure that the adhesives and substrates are at 60°F or higher. If surfaces are porous, a second coat is recommended after the first has dried and become tacky.

## STORAGE

After use, do not close the valve. Leave the gun and hose connected to the canister. Recommended to store canister off the floor if temperatures below 60°F.

## PHYSICAL PROPERTIES

Appearance:	Liquid, clear, red
Specific Gravity:	.75 + .05
Shear Adhesion:	>100psi and >150°F
Spray Tip:	ES6501
Flammability:	Flammable per ASTM E-681-04
Solvent:	Hydrocarbon blend
Shelf Life:	15 months
Freezing:	Not damaged by freezing but return to room temp before use.

## PACKAGING

EB70-013C(R)	13 oz Aerosol Can
EB70-009C(R)	9 lbs Disposable Canister
EB70-270C(R)	27 lbs Disposable Canister
EB70-140C(R)	140 lbs Returnable Canister
EB70-270C(R)	270 lbs Returnable Canister

All in Clear (C) or Red (R) packaging

## KEY FEATURES

- ★ Temporary or Permanent Bonds
- ★ Water Resistant
- ★ Fast Tack
- ★ No Chlorinated Solvents
- ★ No ODS (Ozone Depleting Substances)



**Disclaimer of Warranty:** NewStar Adhesives Inc. expressly disclaims all warranties either expressed or implied, including but not limited to merchantability and fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost, at our discretion. This provision relates to all sales and cannot be modified.

**Manufacturer:** NewStar Adhesives Inc., [gluepros@newstaradhesives.com](mailto:gluepros@newstaradhesives.com), 866-735-9876

See MSDS Data Sheet for Proper Handling and Safety Information

