

EB80

HIGH STRENGTH
CONTACT ADHESIVE

CA Compliant

Long Open Time

Low Odor

SCAQMD Rule 1168 &
OTC Compliant

LEED Compliant

EverBond Fast Tack
Bond Performance

Web Spray Pattern

No ODS

No HAPS

EVERBOND
PREMIUM • ADHESIVES

CA COMPLIANT

EverBond EB80 is a high strength contact adhesive with excellent performance characteristics. Applied on both surfaces to be adhered, EB80 is a high strength, high temperature contact adhesive providing strong permanent bonds for a wide variety of substrates to include decorative laminates and veneers, fiberglass, glass, upholstery, fabrics, foam, auto headliners, cork and particle board. As a single surface application, its high tack and repositionability make EB80 an ideal adhesive for quick temporary bonding. Formulated with extremely low VOCs to comply with CA and OTC states regulations.

PRODUCT USAGE

For strong permanent bonds, apply EB80 to both surfaces to be bonded. For repositionable temporary bonds, apply EverBond EB80 evenly to one side of the substrates to be bonded. Spray an even coat of adhesive with at least 80% to 100% coverage. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease or oil. Ensure that the adhesives and substrates are at 60°F or higher.

STORAGE

After use, do not close the valve. Leave the gun and hose connected to the canister. Recommended to store canister off the floor if temperatures below 60°F.

PHYSICAL PROPERTIES

Appearance:	Liquid, clear or red
Specific Gravity:	0.85 - 0.95 g/cc
Shear Adhesion:	100psi >200°F
Spray Tip:	ES6501
Spray Pattern:	Web Spray
Flammability:	Flammable per ASTM E-681-04
VOC:	5 - 10% by weight, 65 - 75 gm/cc
Shelf Life:	15 months
Freezing:	Not damaged by freezing but return to room temp before use.

PACKAGING

EB80-013C(R)	13 oz Aerosol Can
EB80-009C(R)	9 lbs Disposable Canister
EB80-027C(R)	27 lbs Disposable Canister
EB80-140C(R)	140 lbs Returnable Canister
EB80-270C(R)	270 lbs Returnable Canister
EB80-005C(R)	5 gal Pail
EB80-055C(R)	55 gal Drum

All available in Clear (C) or Red (R)

Disclaimer of Warranty: NewStar Adhesives Inc. expressly disclaims all warranties either expressed or implied, including but not limited to merchantability and fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost, at our discretion. This provision relates to all sales and cannot be modified.

Manufacturer: NewStar Adhesives Inc., gluepros@newstaradhesives.com, 866-735-9876

See MSDS Data Sheet for Proper Handling and Safety Information

KEY FEATURES

- ★ CA Compliant
- ★ Long Open Time
- ★ Low Odor
- ★ SCAQMD Rule 1168 & OTC Compliant
- ★ LEED Compliant
 - LEED Schools EQ Credit 4.0
 - LEED Core & Shell EQ Credit 4.0
 - LEED ND & CI EQ Credit 4.1
 - LEED EB MR Credit 3.0
- ★ EverBond Fast Tack Bond Performance
- ★ Web Spray Pattern

