

# EB900

HIGH SOLIDS  
POSTFORMABLE SPRAY  
GRADE CONTACT ADHESIVE

Spray Grade

EverBond Bond  
Performance

High Temperature  
Resistance

Fast Tack

Postformable

**EVERBOND**  
PREMIUM • ADHESIVES

EverBond EB900 is a high solids spray grade neoprene based contact adhesive designed for postforming and production efficiency. It is suitable for permanently bonding a wide range of materials. Water resistant and temperature resistant to over 200°F. Suitable for most production postforming applications.

## PRODUCT USAGE

EverBond EB900 is designed to be applied to both surfaces about to be joined. Spray an even coat of adhesive on both surfaces. Allow to tack. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease or oil. Ensure that the adhesives and substrates are at 60°F or higher. If assembly is delayed and the adhesive becomes too dry, apply a light coating again.

## STORAGE

Store in clean, dry area away from sparks and heat sources. Recommended to store container off the floor if temperatures below 60°F.

## PHYSICAL PROPERTIES

Appearance:	Liquid, clear or red
Base:	Neoprene
Solvent:	Blend of hydrocarbons & ketones
Solids %:	19 – 21%
Density:	6.9 lb/gal
Flash point:	> -0°F
Shelf Life:	12 months (unopened)
Freezing:	Not damaged by freezing but return to room temp & stir before use.

## PACKAGING

EB900-005C(R)	5 gal Pail
EB900-055C(R)	52 gal Drum

All available in Clear (C) or Red (R)

## KEY FEATURES

- ★ Spray Grade
- ★ EverBond Bond Performance
- ★ High Temperature Resistance
- ★ Fast Tack
- ★ Postformable



**Disclaimer of Warranty:** NewStar Adhesives Inc. expressly disclaims all warranties either expressed or implied, including but not limited to merchantability and fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost, at our discretion. This provision relates to all sales and cannot be modified.

**Manufacturer:** NewStar Adhesives Inc., gluepros@newstaradhesives.com, 833-216-6627

See MSDS Data Sheet for Proper Handling and Safety Information

