# N680

**CA Compliant** 

**Long Open Time** 

**Low Odor** 

SCAQMD Rule 1168 & OTC Compliant

**LEED Compliant** 

**Fast Tack** 

**Strong Bonds** 



CA COMPLIANT
OTC COMPLIANT

EverHold N680 is a high strength contact adhesive with excellent performance characteristics. Applied on both surfaces to be adhered, N680 is a high strength, high temperature contact adhesive providing strong permanent bonds for carpets and a wide variety of substrates to include decorative laminates and veneers, fiberglass, glass, upholstery, fabrics, foam, headliners, cork and particle board. As a single surface application, its high tack and repositionability make N680 an ideal adhesive for quick temporary bonding. Formulated with extremely low VOCs to comply with CA and OTC states regulations.

# PRODUCT USAGE

For strong permanent bonds, apply N680 to both surfaces to be bonded. For repositionable temporary bonds, apply EverHold N680 evenly to one side of the substrates to be bonded. Spray an even coat of adhesive with at least 80% to 100% coverage. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease or oil. Ensure that the adhesives and substrates are at 60°F or higher.

# STORAGE

After use, do not close the valve. Leave the gun and hose connected to the canister. Recommended to store canister off the floor if temperatures below  $60^{\circ}F$ .

## PHYSICAL PROPERTIES

Appearance: Liquid, clear or red

Specific Gravity: .95 + .02
Shear Adhesion: 100psi >200°F
Spray Tip: ES6501
Spray Pattern: Web Spray

Flammability: Flammable per ASTM E-681-04

VOC: <80g/l, EPA Method 24, No ODS, No HAPS

Shelf Life: 15 months

Freezing: Not damaged by freezing but return to room

temp before use.

## PACKAGING

N680-009C9 lbs Disposable CanisterN680-027C27 lbs Disposable CanisterN680-140C140 lbs Returnable CanisterN680-270C270 lbs Returnable Canister

All available in Clear (C)

### KEY FEATURES

- **★** CA Compliant
- ★ Long Open Time
- ★ Low Odor
- ★ SCAQMD Rule 1168 & OTC Compliant
- **★ LEED Compliant** 
  - -LEED Schools EQ Credit 4.0
  - -LEED Core & Shell EQ Credit 4.0
  - -LEED ND & CI EQ Credit 4.1
  - -LEED EB MR Credit 3.0
- ★ Fast Tack



**Disclaimer of Warranty:** NewStar Adhesives Inc. expressly disclaims all warranties either expressed or implied, including but not limited to merchantability and fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost, at our discretion. This provision relates to all sales and cannot be modified.

Manufacturer: NewStar Adhesives Inc., gluepros@newstaradhesives.com, 855-497-0700

See MSDS Data Sheet for Proper Handling and Safety Information

