

N614

Flammable DOT

No ODS

Non-Chlorinated Solvent

EverStrong™ Superior
Bond Performance

Fast Tack

Water Resistant

EVERHOLD

NAUTICAL • ADHESIVES

EverHold N614 is a high performance and versatile industrial strength contact adhesive specifically designed for construction applications. Water resistant and temperature resistant to 200°F, N614 is designed for bonding a wide range of substrates that include foundation insulation, ABS tub surrounds, fiberglass, glass, upholstery, fabrics, foam, cork, particle board, and wood.

PRODUCT USAGE

EverHold N614 is designed to be applied to both surfaces about to be joined. Spray an even coat of adhesive with at least 80% to 100% coverage of each surface. Allow to dry 2-4 minutes until tacky. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease or oil. If surfaces are porous, a second coat is recommended after the first has dried and become tacky.

STORAGE

After use, do not close the valve. Leave the gun and hose connected to the canister. Recommended to store canister off the floor if temperatures below 60°F.

PHYSICAL PROPERTIES

Appearance:	Liquid, clear or red
Specific Gravity:	.74 + .03
Spray Tip:	Q tip
Spray Pattern:	Web Spray
Flammability:	Flammable per ASTM E-681-04
Solvent:	Hydrocarbons
Shelf Life:	15 months
Freezing:	Not damaged by freezing but return to room temp before use.

PACKAGING

N614-009C(R)	9 lbs Disposable Canister
N614-028C(R)	28 lbs Disposable Canister
N614-140C(R)	140 lbs Returnable Canister
N614-290C(R)	290 lbs Returnable Canister

All available in Clear (C) or Red (R)

KEY FEATURES

- ★ No ODS (Ozone depleting substances)
- ★ Non-Chlorinated Solvent
- ★ EverStrong™ Superior Bond Performance
- ★ Fast Tack
- ★ Water Resistant



Disclaimer of Warranty: NewStar Adhesives Inc. expressly disclaims all warranties either expressed or implied, including but not limited to merchantability and fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost, at our discretion. This provision relates to all sales and cannot be modified.

Manufacturer: NewStar Adhesives Inc., gluepros@newstaradhesives.com, 855-497-0700

See MSDS Data Sheet for Proper Handling and Safety Information

N614-1

