ES10

BULK ADHESIVE

Spray Grade

EverStrong™ Bond Performance

High Temperature Resistance

SCAQMD Compliant

OTC Compliant



EverStrong™ ES10 is a high solids spray grade contact adhesive that meets SCAQMD and OTC requirements. It is suitable for permanently bonding a wide range of materials including decorative laminates, edgebanding, veneers, glass, fiberglass, headliners, fabric, particle board and many plastics. Water resistant and temperature resistant to over 200°F.

PRODUCT USAGE

EverStrong™ ES10 is designed to be applied to both surfaces about to be joined. Spray an even coat of adhesive approximately 3-5 mils thick on both surfaces. Allow to tack. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease or oil. Ensure that the adhesives and substrates are at 60°F or higher. If assembly is delayed and the adhesive becomes too dry, apply a light coating again.

STORAGE

Store in clean, dry area away from sparks and heat sources. Recommended to store container off the floor if temperatures

PHYSICAL PROPERTIES

Appearance: Liquid, clear or red Base: Synthetic polymers

Solids %: 32 - 34%Density: 7.8 lb/galFlash point: $14^{\circ}\text{F} (-10^{\circ}\text{C})$

Shelf Life: 12 months (unopened)

Freezing: Not damaged by freezing but return to room

temp & stir before use.

PACKAGING

ES10-005C(R) 5 gal Pail
ES10-055C(R) 55 gal Drum
All available in Clear (C) or Red (R)

KEY FEATURES

- ★ Spray Grade
- **★** EverStrong[™] Bond Performance
- ★ High Temperature Resistance
- **★** SCAQMD Compliant
- **★** OTC Compliant

Disclaimer of Warranty: NewStar Adhesives Inc. expressly disclaims all warranties either expressed or implied, including but not limited to merchantability and fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost, at our discretion. This provision relates to all sales and cannot be modified.

Manufacturer: NewStar Adhesives Inc., gluepros@newstaradhesives.com, 855-497-0700

See MSDS Data Sheet for Proper Handling and Safety Information

