

ES10+ AEROSOL



Meets 2017 CARB Requirements

No HAPS, No ODS

OTC Compliant

LEED Compliant

Flammable DOT

Postformable

EverStrong™ Bond Performance

Fast Tack

High Temperature resistance

MEETS 2017 CARB REQUIREMENTS

EverStrong™ ES10+ aerosol adhesive is a high performance industrial contact adhesive formulated to comply with 2017 CARB Regulations. Water resistant and temperature resistant to over 200°F, ES10+ is designed for bonding a wide range of substrates to include decorative laminates and veneers, fiberglass, glass, upholstery, fabrics, foam, auto headliners, cork and particle board.

PRODUCT USAGE

EverStrong™ ES10+ is designed to be applied to both surfaces about to be joined. Spray an even coat of adhesive with at least 80% to 100% coverage of each surface. Allow to dry 3-5 minutes til tacky. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease or oil. Ensure that the adhesives and substrates are at 60°F or higher. If surfaces are porous, a second coat is recommended after the first has dried and become tacky.

STORAGE

Recommended to store off the floor if temperatures below 60°F.

PHYSICAL PROPERTIES

Appearance:	Liquid, clear or red
Specific Gravity:	.72 – .80 g/cc
Shear Adhesion:	>100psi and >200°F
Spray Pattern:	Web Spray
Flammability:	Flammable per ASTM E-681-04
VOC:	< 40%
Shelf Life:	15 months
Freezing:	Not damaged by freezing but return to room temp before use.

PACKAGING

ES10-013C(R) 13 oz Aerosol Can

All available in Clear (C) or Red (R)

KEY FEATURES

- ★ Meets 2017 CARB Requirements
- ★ No HAPS, No ODS
- ★ LEED Compliant
 - LEED Schools EQ Credit 4.0
 - LEED Core & Shell EQ Credit 4.0
 - LEED ND & CI EQ Credit 4.1
 - LEED EB MR Credit 3.0
 - MR Credit 5.1 (specific projects must be evaluated)
- ★ EverStrong™ Fast Tack Bond Performance
- ★ High Temperature resistance

Disclaimer of Warranty: NewStar Adhesives Inc. expressly disclaims all warranties either expressed or implied, including but not limited to merchantability and fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost, at our discretion. This provision relates to all sales and cannot be modified.

Manufacturer: NewStar Adhesives Inc., gluepros@newstaradhesives.com, 855-497-0700

See MSDS Data Sheet for Proper Handling and Safety Information

ES10+-2

