

ES110

CONTACT ADHESIVE

Specifically designed for
Air Assist Spray

No VOCs

SCAQMD Rule 1168 &
OTC Compliant

LEED Compliant

No VOCs

Postformable

High Temperature
Resistant

No ODS

No HAPS



EVERSTRONG
ADHESIVE

CA COMPLIANT
AIR ASSIST SPRAY

EverStrong™ ES110 is a multi-purpose industrial contact adhesive specifically designed for air assist spray application. Applied on both surfaces to be adhered, ES110 is a high strength, high temperature contact adhesive providing strong permanent bonds for a wide variety of substrates to include decorative laminates and veneers, fiberglass, glass, upholstery, fabrics, foam, auto headliners, cork and particle board. Formulated with extremely low VOCs to comply with CA and OTC states regulations.

PRODUCT USAGE

For strong permanent bonds, apply ES110 to both surfaces to be bonded. Spray an even coat of adhesive with at least 80% to 100% coverage. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease or oil. Ensure that the adhesives and substrates are at 60°F or higher.

STORAGE

After use, do not close the valve. Leave the gun and hose connected to the canister. Recommended to store canister off the floor if temperatures below 60°F.

PHYSICAL PROPERTIES

Appearance:	Liquid, clear or red
Specific Gravity:	.90 - .94 g/cc
Shear Adhesion:	100psi >200°F
Spray Pattern:	Pebble Spray
Flammability:	Flammable per ASTM E-681-04
VOC:	0% by weight
Shelf Life:	15 months
Freezing:	Not damaged by freezing but return to room temp before use.

PACKAGING

ES110-008C(R)	8# Disposable Canister
ES110-027C(R)	27# Disposable Canister
ES110-130C(R)	130# Returnable Canister
ES110-270C(R)	270# Returnable Canister

All available in Clear (C) or Red (R)

Disclaimer of Warranty: NewStar Adhesives Inc. expressly disclaims all warranties either expressed or implied, including but not limited to merchantability and fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost, at our discretion. This provision relates to all sales and cannot be modified.

Manufacturer: NewStar Adhesives Inc., gluepros@newstaradhesives.com, 855-497-0700

See MSDS Data Sheet for Proper Handling and Safety Information

ES110-4

KEY FEATURES

- ★ Specifically designed for Air Assist Spray
- ★ No VOCs
- ★ SCAQMD Rule 1168 & OTC Compliant
- ★ LEED Compliant
 - LEED Schools EQ Credit 4.0
 - LEED Core & Shell EQ Credit 4.0
 - LEED ND & CI EQ Credit 4.1
 - LEED EB MR Credit 3.0

