

ESW11

WATER BASED
CONTACT ADHESIVE

Robust, Easy to Use

EverStrong™ Bonds

High Temperature
Resistance

Non-Flammable

LEED Compliant

SCAQMD and
OTC Compliant



EVERSTRONG™
A D H E S I V E

EverStrong™ ESW11 is a versatile, robust water based contact adhesive designed to provide strong permanent bonds on a wide range of materials to include decorative laminates and veneers, fiberglass, glass, cork, particle board and foam. It will not attack cells in expanded styrene and other foam materials. Water resistant and temperature resistant to over 200°F. Recommended for flat work.

PRODUCT USAGE

EverStrong™ ESW11 is designed to be applied to both surfaces about to be joined. Spray or roll an even coat of adhesive on both surfaces. Allow to tack. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease or oil. Ensure that the adhesives and substrates are at 60°F or higher.

STORAGE

Store in clean, dry area. Protect from freezing.

PHYSICAL PROPERTIES

Appearance:	Liquid, white or red
Base:	Synthetic polymers
Solvent:	Water based, no solvents
Solids %:	43.0 - 47.0%
Density:	8.80 - 9.20 lb/gal
Flash point:	none
Shelf Life:	12 months (unopened)
Freezing:	Protect from freezing.

PACKAGING

ESW11-001C(R)	4-1 gal Pails
ESW11-005C(R)	5 gal Pail
ESW11-055C(R)	55 gal Drum

All available in Clear (C) or Red(R)

KEY FEATURES

- ★ Robust, Easy to Use
- ★ EverStrong™ Bonds
- ★ High Temperature Resistance
- ★ Non-Flammable
- ★ LEED Compliant
- ★ SCAQMD and OTC Compliant

Disclaimer of Warranty: NewStar Adhesives Inc. expressly disclaims all warranties either expressed or implied, including but not limited to merchantability and fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost, at our discretion. This provision relates to all sales and cannot be modified.

Manufacturer: NewStar Adhesives Inc., gluepros@newstaradhesives.com, 855-497-0700

See MSDS Data Sheet for Proper Handling and Safety Information

ESW11-2

