PT1Y

Fast Setting High Tack

Solvent free

SCAQMD Rule 1168 &OTC Compliant

OSHA Compliant (29CFR 1910.1200)

Strong Bonds

High Temperature Resistance

Non-Flammable

Easy to sand and paint



PT1Y is a superior wood glue for interior woodworking such as cabinetry and furniture. Designed to bond softwoods, hardwoods and composites, it is an excellent adhesive for assembly, doweling, edge or face gluing. Its strong initial tack and strong bond strength make it excellent for wood repairs.

PRODUCT USAGE

Pionite PT1Y is designed to be applied to one surface then assembled and clamped for at least 30 minutes. For best results: Make sure that the surfaces are dry and free from dirt, grease or oil. Ensure that the adhesives and substrates are at 50°F or higher. Wipe all excess glue with clean moist cloth. Not recommended for Exterior use or wet, high moisture conditions.

STORAGE

After use, close container tightly. Store in cool dry location at 50-80°F. Protect from freezing.

PHYSICAL PROPERTIES

Appearance: Yellow Liquid
Specific Gravity: 1.07 to 1.11 gm/cc
Solvent: Water based, no solvents

Flashpoint: > 200°F

Flammability: Non-Flammable per ASTM 681-04

Shelf Life: 12 months

Freezing: Protect from freezing.

KEY FEATURES

- · Fast Setting High Tack
- · Solvent free
- SCAQMD Rule 1168 & OTC Compliant
- OSHA Compliant (29CFR 1910.1200)
- Strong Bonds
- · High Temperature Resistance
- · Non-Flammable
- · Easy to sand and paint

PACKAGING

PT1Y-001 4-1 gal Jugs PT1Y-005 5 gal Pail PT1Y-055 55 gal Drum

Disclaimer of Warranty: Pionite expressly disclaims all warranties either expressed or implied, including but not limited to merchantability and fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost, at our discretion. This provision relates to all sales and cannot be modified.

Mfd. for: Pionite (855) 497-0700

See MSDS Data Sheet for Proper Handling and Safety Information