

# Safety Data Sheet

## ES 900 bulk

Date Issued: March 23, 2022

Revision No: 3

Supersedes Date: June 6, 2021

### Section 1. Product Description

1.1 Product Name: EverStrong ES 900 bulk Contact Adhesive

1.2 Recommended Use: Industrial adhesive applications

1.3 Manufacturer: and address: NewStar Adhesives Inc  
66 Gilreath Rd SE  
Cartersville, GA 30121

Information Contact: PH 866-735-9876 FX 770-607-3637

Emergency Contact: 800-424-9300 (CHEMTREC- Transportation Spill Response 24 hours)

### Section 2. Hazard Identification

Classification in accordance

2.1 Hazard Classification

Flammable Liquid: Category 2

Serious Eye Damage/Irritation: Category 2A

Skin Corrosion/Irritation: Category 2

Carcinogenicity: Category 2A

Simple Asphyxiant

Specific Target Organ Toxicity (single exposure): Category 3

2.2.1 Label elements

Signal Word: Danger

**DANGER**

### Symbols



### Hazard Statements:

Extremely flammable liquid and vapor.

Causes serious eye irritation.

Causes skin irritation.

May cause drowsiness or dizziness.

May displace oxygen and cause rapid suffocation.

Causes damage of organs: Cardiovascular system.

## PRECAUTIONARY STATEMENTS:

### Prevention:

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces – No smoking.  
Ground/bond container and receiving equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Keep containers tightly closed.  
Use explosion proof electrical/ventilating/lighting equipment.  
Do not breathe dust/fumes/gas/vapor/mist/spray.  
Use only outdoors or in well ventilated area.  
Wear protective clothing and eye/face protection.  
Do not eat, drink, or smoke when using this product.  
Wash thoroughly after handling.

### Response

**IF INHALED:** Remove to fresh air and keep comfortable for breathing.

**IF ON SKIN (OR HAIR):** Take off immediately all contaminated clothing. Rinse skin with water and shower. If irritation persists, seek medical attention. Continue to rinse.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lens, if present and easy to do. Continue rinsing. If irritation persists seek medical attention.

### STORAGE

Protect from sunlight.  
Keep cool.  
Keep container tightly closed.  
Store locked up in a well-ventilated place.

### DISPOSAL

Dispose of contents/container in accordance with local/regional/national/international regulations.

## **Section 3. Composition/ Information on Ingredients**

Chemical Name	C.A.S.	
	Number	%
Acetone	67-64-1	30 – 40 %
Heptane	142-82-5	5 - 15 %
Hexane	110-54-3	20 - 30 %
Toluene	108 -88-3	5 – 15 %

## **Section 4. First Aid Measures**

**Skin Contact:** Wash with plenty of water. Wash contaminated clothing after use.

**Inhalation:** Remove person to fresh air and keep comfortable for breathing. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek medical assistance. If breathing has stopped, give artificial respiration.

**Eyes:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

**Ingestion:** Rinse mouth. If you feel unwell get medical advice/attention.

## **Section 5. Firefighting Procedures**

**Extinguishing Media:** Use water spray, dry chemical, CO<sub>2</sub>, or appropriate foam.

In case of fire, use a fire fighting agent for flammable liquid.

**Hazardous decomposition or by product:** Aldehydes, hydrocarbons, carbon monoxide and carbon dioxide, ketones, oxides of nitrogen, sulfur and other toxic vapor, gas, and particulate.

**Special protective actions for fire-fighters:** Keep containers cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, bunker coat and pants, face mask, and protective covering for exposed area of head.

## **Section 6. Accidental Release Measures**

**Personal Precautions:** Use personal protective equipment. Avoid breathing vapors, mist, or vapors. Ensure adequate ventilation. Remove all sources of ignition. Vapors can accumulate in low areas.

**Environmental Precautions:** Prevent further leakage or spillage if safe to do so.

**Clean-Up:** Cover with commercially available nonflammable inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Collect waste and dispose of in accordance with all applicable local/state/federal regulations.

## **SECTION 7. Handling and Storage**

**Handling:** Avoid breathing vapors. Use personal protection equipment as required. In case of inadequate ventilation wear respiratory protection. Do not eat, drink, or smoke when using this product. Wash contaminated clothing and skin after use.

**Storage:** Store in a well-ventilated space. Protect from direct sunlight.

## **SECTION 8. Protection Information**

<b>Hazardous Component</b>	<b>Authority</b>	<b>Type</b>	<b>Limit</b>
Acetone	ACGIH	TWA	500 ppm
Acetone	OSHA	TWA	750 ppm
Heptane	ACGIH	TWA	400 ppm
Heptane	OSHA	TWA	750 ppm
Heptane	STEL	TWA	500 ppm
Toluene	ACGIH	PPM	150 ppm
Toluene	OSHA	TWA	50 ppm
Hexane	OSHA	TWA	750 ppm
Hexane	OSHA	TWA	50 ppm
Pentane	OSHA	TWA	1000 ppm

### **SOURCES OF EXPOSURE LIMIT DATA:**

**ACGIH:** American Conference of Governmental Industrial Hygienists

**CMRG:** Chemical Manufacturer Recommended Guideline

**EPA:** Environmental Protection Agency

**IARC:** International Agency for the Research on Cancer

**NIOSH:** National Institute for Occupational Safety and Health

**NTP:** National Toxicology Program

**OSHA:** Occupational Safety and Health Administration

**WEEL** Workplace Environmental Exposure Level

### **Control Parameters**

**Engineering Measures:** Ensure adequate ventilation, especially in confined areas.

### **Personal Protective Equipment (PPE):**

**Eyes/Face:** Safety goggles or safety glasses with side shields.

**Skin:** Protective gloves such as Viton, PVA or equivalent and impervious clothing.

**Respiratory:** In operations where exposure limits are exceeded, use a NIOSH approved respirator suitable for the specific work conditions.

**Hygiene:** Avoid contact with skin, eyes, and clothing. Wash promptly with soap and water if skin becomes contaminated. Remove and wash contaminated clothing after use. Do not eat, drink, or smoke when using.

## **SECTION 9. Physical Data**

Odor, Color: Organic solvent odor, clear or red in color  
Boiling point: - 133 F  
Vapor Pressure – 245.3 hPa at 39.5 C  
Vapor Density – 0.786 gm/cc  
Specific Gravity: 0.85 - 0.95 g/cc  
VOC less water less exempt and solvents: 4.76 lbs./gal  
Solubility in Water: Negligible  
Volatile Organic Compounds: Not determined  
Flash Point: - 17 C  
Upper Explosion Limit – 13 %  
Lower Explosion Limit – 2.0 %

## **SECTION 10. Stability and Reactivity**

**Chemical Stability:** Stable under normal conditions.

**Conditions to Avoid:** Avoid high temperatures.

**Incompatible Materials:** None known.

**Hazardous Polymerization:** Will not occur.

**Hazardous By-Products:** Combustion may result in formation of aldehydes, hydrocarbons, carbon monoxide and carbon dioxide.

## **SECTION 11. Toxicological Information**

**Typical Routes of Entry:** Inhalation, skin absorption, eye contact

**Aspiration Hazard:** No data

**Acute toxicity:** No data

**Irritation:** No data

**Corrosivity:** No data

**Sensitization:** No data

## **SECTION 12. Ecological Data**

Overview: Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.

Chemical fate information: No data

## **SECTION 13. Disposal Considerations**

Waste Disposal Method:

Dispose of in accordance with all applicable local/regional/national/international/state/federal regulations.

## **SECTION 14. Transportation Information**

DOT Proper Shipping Name:

Adhesive, Flammable Liquid

Hazard Class: 3

UN #: UN1133

Packing Group: II

Label: DOT Red Diamond, (Flammable Liquid), 3

## **SECTION 15. Regulatory Information**

311/312 Hazard Categories:

Fire Hazard – Yes

Reactivity Hazard – No

Immediate Hazard – Yes

Delayed Hazard – Yes

STATE REGULATIONS:

CALIFORNIA PROPOSITION 65:

This product contains Toluene and Hexane, known to the state of California to cause birth defects and other reproductive harm.

HMIS Hazard Rating – NFPA Hazard classification

0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme

Health: 2

Flammability: 3

Reactivity: 0

Special Hazard: None

## **SECTION 16. Other Information**

**DISCLAIMER:** The information in this Material Safety Data Sheet (SDS) is believed to be correct as of the date issued. NEWSTAR MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. The user is responsible for determining whether the NEWSTAR product is fit for a particular purpose and suitable for users' method of use or application, given the variety of factors that can affect the use and application of a NEWSTAR product, many of which are solely within the user's knowledge and control. It is essential that the user evaluate the NEWSTAR product to determine whether it is fit for a particular purpose and suitable for users' method of use or application.