Safety Data Sheet

N681

Date Issued: March 16, 2023 Revision No: 2 Supersedes Date: August 22, 2022

Section 1.

Product Description

 1.1 Product Name: EverHold N681 Mold Release Agent
 1.2 Recommended Use: Industrial applications
 1.3 Manufacturer: and address: NewStar Adhesives Inc 66 Gilreath Rd SE Cartersville, GA 30121
 Information Contact: PH 866-735-9876 FX 770-607-3637
 Emergency Contact: 800-424-9300 (CHEMTREC- Transportation Spill Response 24 hours)

Section 2.

Hazard Identification

Classification in accordance with OSHA Standard 29CFR 1910.1200

2.1 Hazard Classification
Flammable Liquid: Category 1
Serious Eye Damage/Irritation: Category 2A
Skin Corrosion/Irritation: Category 2
Carcinogenicity: Category 2A
Simple Asphyxiant
Specific Target Organ Toxicity (single exposure): Category 3

2.2.1 Label elements Signal Word: Danger

DANGER

Symbols



Hazard Statements: Extremely flammable liquid and vapor.

Causes serious eye irritation. Causes skin irritation. May cause drowsiness or dizziness. May displace oxygen and cause rapid suffocation. Causes damage of organs: Cardiovascular system.

PRECAUTIONARY STATEMENTS:

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces – No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep containers tightly closed. Use explosion proof electrical/ventilating/lighting equipment. Do not breathe dust/fumes/gas/vapor/mist/spray. Use only outdoors or in well ventilated areas. Wear protective clothing and eye/face protection. Do not eat, drink, or smoke when using this product. Wash thoroughly after handling.

Response

IF INHALED: Remove to fresh air and keep comfortable for breathing.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water and shower. If irritation persist, seek medical attention. Continue to rinse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lens if present and easy to do. Continue rinsing. If irritation persist, seek medical attention.

STORAGE

Protect from sunlight. Keep cool. Keep container tightly closed. Store locked up in a well-ventilated place.

DISPOSAL

Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 3.	Composition/Information on Ingredients		
	C.A.S.		
Chemical Name	Number	%	
Methyl Acetate	79-20-9	50 – 60%	
Pentane	109-66-0	5 - 15 %	
Propane	75-28-5	< 5 %	
Isobutane	74-98-6	< 5 %	

Section 4. First Aid Measures

Skin Contact: Wash with plenty of water. Wash contaminated clothing after use.

Inhalation: Remove person to fresh air and keep comfortable for breathing. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek medical assistance. If breathing has stopped, give artificial respiration.

Eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

Ingestion: Rinse mouth. If you feel unwell get medical advice/attention.

Section 5. Firefighting Procedures

Extinguishing Media: Use water spray, dry chemical, CO2, or appropriate foam.

In case of fire, use a firefighting agent for flammable liquid.

Hazardous decomposition or by product: Aldehydes, hydrocarbons, carbon monoxide and cardon dioxide, ketones, oxides of nitrogen, sulfur and other toxic vapor, gas, and particulate.

Special protective actions for fire-fighters: Keep containers cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, bunker coat and pants, face mask, and protective covering for exposed area of head.

Section 6.

Accidental Release Measures

Personal Precautions: Use personal protective equipment. Avoid breathing vapors, mist, or gas. Ensure adequate ventilation. Remove all sources of ignition. Vapors can accumulate in low areas.

Environmental Precautions: Prevent further leakage or spillage if safe to do so.

Clean-Up: Cover with commercially available nonflammable inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Collect waste and dispose of in accordance with all applicable local/state/federal regulations.

SECTION 7. Handling and Storage

Handling: Avoid breathing vapors. Use personal protection equipment as required. In case of inadequate ventilation wear respiratory protection. Do not eat, drink, or smoke when using this product. Wash contaminated clothing and skin after use.

Storage: Store in a well-ventilated space. Protect from direct sunlight.

SECTION 8. Protection Information

Hazardous Component	Authority	Туре	Limit
Methyl Acetate	OSHA	TWA	200 ppm
Methyl Acetate	ACGIH	TWA	250 ppm
Methyl Acetate	NIOSH	TWA	200 ppm
Pentane	NIOSH	TWA	120 ppm
Pentane	OSHA	TWA	600 ppm
Propane	OSHA	TWA	1000 ppm
Isobutane	ACGIH	TWA	1000 ppm

SOURCES OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists CMRG: Chemical Manufacturer Recommended Guideline EPA: Environmental Protection Agency IARC: International Agency for the Research on Cancer NIOSH: National Institute for Occupational Safety and Health NTP: National Toxicology Program OSHA: Occupational Safety and Health Administration WEEL: Workplace Environmental Exposure Level

<u>Control Parameters</u> Engineering Measures:

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment (PPE):

Eyes/Face:	Safety goggles or safety glasses with side shields.
Skin:	Protective gloves such as Viton, PVA or equivalent and impervious clothing.
Respiratory:	In operations where exposure limits are exceeded, use a NIOSH approved respirator suitable for the specific work conditions.

Hygiene: Avoid contact with skin, eyes, and clothing. Wash promptly with soap and water if skin becomes contaminated. Remove and wash contaminated clothing after use. Do not eat, drink, or smoke when using.

SECTION 9. Physical Data

Odor, Color: Organic solvent odor, clear or red in color Boiling point: -44° F Vapor Pressure: Not Determined Vapor Density: Not Determined Specific Gravity: 0.85 - 0.95 g/cc Solubility in Water: Negligible Volatile Organic Compounds: 5 – 10 % by weight Volatile Organic Compounds: 65 – 75 g/L Flash Point: -156° F (-104 ° C) LEL: 1.8 % by volume UEL: 18.0 % by volume

SECTION 10. Stability and Reactivity

Chemical Stability: Stable under normal conditions.

Conditions to Avoid: Avoid high temperatures.

Incompatible Materials: None known.

Hazardous Polymerization: Will not occur.

Hazardous By-Products: Combustion may result in formation of aldehydes, hydrocarbons, carbon monoxide and carbon dioxide.

SECTION 11. Toxicological Information

Typical Routes of Entry: Inhalation, skin absorption, eye contact

Aspiration Hazard: No data Acute toxicity: No data Irritation: No data Corrosivity: No data Sensitization: No data

SECTION 12. Ecological Data

Overview: Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.

Chemical fate information: No data

SECTION 13. Disposal Considerations

Waste Disposal Method:

Dispose of in accordance with all applicable local/regional/national/international/state/federal regulations.

SECTION 14. Transportation Information

DOT Proper Shipping Name:

Chemicals Under Pressure, Flammable, N.O.S., (Nitrogen, Methyl Acetate)Hazard Class:2.1UN #:UN3501Packing Group:NoneLabel:DOT Red Diamond 2

SECTION 15. Regulatory Information

311/312 Hazard Categories: Fire Hazard – Yes Pressure Hazard – Yes Reactivity Hazard – No Immediate Hazard – Yes Delayed Hazard – Yes

STATE REGULATIONS: CALIFORNIA PROPOSITION 65: None known.

HMIS Hazard Rating – NFPA Hazard classification 0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme Health: 2 Flammability: 3 Reactivity: 0 Special Hazard: None

SECTION 16. Other Information

DISCLAIMER: The information in this Material Safety Data Sheet (SDS) is believed to be correct as of the date issued. NEWSTAR MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. The user is responsible for determining whether the NEWSTAR product is fit for a particular purpose and suitable for users' method of use or application, given the variety of factors that can affect the use and application of a NEWSTAR product, many of which are solely within the user's knowledge and control. It is essential that the user evaluate the NEWSTAR product to determine whether it is fit for a particular purpose and suitable for users' method of use or application.